



Allied Pressroom Products
Chemicals for the International Printing Industry

SAFETY DATA SHEET

Pressline Blanket Fix (USA)

1. Identification

Product identifier

Product name Pressline Blanket Fix (USA)

Recommended use of the chemical and restrictions on use

Application For use as a blanket treatment in the lithographic printing industry. Blanket treatment.

Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier ALLIED PRESSROOM PRODUCTS
2040 Lee Street
Hollywood
FL 33020
USA
+1 800-327-8487 (09:00-17:00 EST)
+1 954-923-6462
info@alliedchem.com

Manufacturer Same as supplier

Emergency telephone number

Emergency telephone Allied Pressroom Products +1 800-327-8487 (09:00-17:00 EST) 24 HR. EMERGENCY TELEPHONE 800-424-9300 CHEMTREC

National emergency telephone number 911

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Muta. 1B - H340 Carc. 1B - H350 Repr. 2 - H361d STOT SE 1 - H370 STOT SE 3 - H336 STOT RE 2 - H373

Environmental hazards Not Classified

Human health

Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. The liquid is irritating to eyes and skin. Harmful in contact with skin. Harmful if swallowed. Harmful by inhalation. Known or suspected mutagen. Contains a substance/a group of substances which may cause cancer. Contains a substance/a group of substances which may damage fertility and the unborn child. Vapors and spray/mists in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Causes damage to organs (optic nerve, Central nervous system). May cause damage to organs (Liver , Kidneys , Central nervous system , Hearing organs) through prolonged or repeated exposure.

Pressline Blanket Fix (USA)

Environmental


The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Physicochemical

Contains halogenated hydrocarbons Can become highly flammable in use.

Label elements

Pictogram



Signal word

Danger

Hazard statements

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H340 May cause genetic defects.
 H350 May cause cancer.
 H361d Suspected of damaging the unborn child.
 H370 Causes damage to organs .
 H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P201 Obtain special instructions before use.
 P260 Do not breathe vapor/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P308+P313 If exposed or concerned: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P501 Dispose of contents/container in accordance with national regulations.

Contains

DICHLOROMETHANE, METHANOL, Solvent naphtha (petroleum), light aliph., XYLENE, TOLUENE, ETHYLBENZENE, HEPTANE

Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

Hazards not otherwise classified (HNOC)

Can become highly flammable in use.

3. Composition/information on ingredients

Mixtures

DICHLOROMETHANE	30-60%
CAS number: 75-09-2	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
Carc. 2 - H351	
STOT SE 3 - H336	

Pressline Blanket Fix (USA)

METHANOL	10-30%
CAS number: 67-56-1	
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 3 - H301	
Acute Tox. 3 - H311	
Acute Tox. 3 - H331	
STOT SE 1 - H370	
Solvent naphtha (petroleum), light aliph.	10-30%
CAS number: 64742-89-8	
Classification	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
Muta. 1B - H340	
Carc. 1B - H350	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
XYLENE	1-5%
CAS number: 1330-20-7	
Classification	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
STOT SE 3 - H335	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	
TOLUENE	1-5%
CAS number: 108-88-3	
Classification	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
Repr. 2 - H361d	
STOT SE 3 - H336	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	

Pressline Blanket Fix (USA)

ETHYLBENZENE	1-5%
CAS number: 100-41-4	
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H332	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	
HEPTANE	1-5%
CAS number: 142-82-5	
M factor (Acute) = 1	
M factor (Chronic) = 1	
Classification	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	

The Full Text for all Hazard Statements are Displayed in Section 16.

4. First-aid measures

Description of first aid measures

Inhalation	Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately. If breathing stops, provide artificial respiration. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.
Ingestion	Remove affected person from source of contamination. Promptly get affected person to drink large volumes of water to dilute the swallowed chemical. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Do not induce vomiting.
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

General information	Contains a substance/a group of substances which may cause cancer. May cause genetic defects. Contains a substance/a group of substances which may damage fertility and the unborn child. Causes damage to organs (Central nervous system , optic nerve). May cause damage to organs (Central nervous system , Kidneys , Liver , Hearing organs) through prolonged or repeated exposure.
Inhalation	Harmful by inhalation. Drowsiness, dizziness, disorientation, vertigo. Nausea, vomiting. Headache. Upper respiratory irritation. Coughing, chest tightness, feeling of chest pressure. May cause an asthma-like shortness of breath.
Ingestion	Harmful if swallowed. May cause nausea, headache, dizziness and intoxication. May cause unconsciousness, blindness and possibly death. May cause stomach pain or vomiting.

Pressline Blanket Fix (USA)

Skin contact Prolonged contact may cause redness, irritation and dry skin. Harmful in contact with skin. This product is rapidly absorbed through the skin and may cause symptoms similar to those of ingestion. Burns can occur.

Eye contact Severe irritation, burning and tearing. May cause blurred vision and serious eye damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Special hazards arising from the substance or mixture

Specific hazards Thermal decomposition or combustion products may include the following substances: Very toxic or corrosive gases or vapors. May form explosive or toxic mixtures with air.

Hazardous combustion products Fire creates: Hydrogen chloride (HCl). Carbon monoxide (CO). Carbon dioxide (CO₂). Phosgene (COCl₂).

Advice for firefighters

Protective actions during firefighting Control run-off water by containing and keeping it out of sewers and watercourses. Cool containers exposed to flames with water until well after the fire is out. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Provide adequate ventilation. Avoid contact with skin or inhalation of spillage, dust or vapour. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses.

Reference to other sections For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapors, spray or mist. Keep away from heat, sparks and open flame.

Conditions for safe storage, including any incompatibilities

Storage precautions May attack some plastics, rubber and coatings. Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Pressline Blanket Fix (USA)

Storage class Toxic storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

DICHLOROMETHANE

Short-term exposure limit (15-minute): OSHA 125 ppm

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm 174 mg/m³

A3

METHANOL

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 262 mg/m³

Long-term exposure limit (8-hour TWA): OSHA 200 ppm 260 mg/m³

Short-term exposure limit (15-minute): ACGIH 250 ppm 328 mg/m³

Sk

Solvent naphtha (petroleum), light aliph.

ACGIH - TWA 300ppm / 1370 mg/m³

OSHA - TWA 500ppm / 2000 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): ACGIH 100 ppm 434 mg/m³

Long-term exposure limit (8-hour TWA): OSHA 100 ppm 435 mg/m³

Short-term exposure limit (15-minute): ACGIH 150 ppm 651 mg/m³

A4

TOLUENE

Long-term exposure limit (8-hour TWA): ACGIH 20 ppm 75 mg/m³

Long-term exposure limit (8-hour TWA): OSHA 200 ppm

Ceiling exposure limit: OSHA 300 ppm

A4

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): OSHA 100 ppm 435 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 20 ppm 87 mg/m³

A3

HEPTANE

Long-term exposure limit (8-hour TWA): OSHA 500 ppm 2000 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 400 ppm 1640 mg/m³

Short-term exposure limit (15-minute): ACGIH 500 ppm 2050 mg/m³

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

A4 = Not Classifiable as a Human Carcinogen.

Sk = Danger of cutaneous absorption.

DICHLOROMETHANE (CAS: 75-09-2)

DNEL

Workers - Inhalation; Long term systemic effects: 353 mg/m³ Workers - Dermal;
Long term systemic effects: 12 mg/kg/day

Pressline Blanket Fix (USA)

PNEC - Fresh water; 0.31 mg/l - Marine water; 0.031 mg/l - Intermittent release; 0.27 mg/l - STP; 26 mg/l - Sediment (Freshwater); 0.26 mg/kg - Sediment (Marinewater); 0.26 mg/kg - Soil; 0.33 mg/kg

Immediate danger to life and health 2300 ppm

METHANOL (CAS: 67-56-1)

DNEL Industry - Inhalation; Short term systemic effects: 260 mg/m³ Industry - Dermal; Short term systemic effects: 40 mg/kg/day Industry - Inhalation; Short term local effects: 260 mg/kg/day Industry - Inhalation; Long term local effects: 260 mg/m³ Industry - Inhalation; Long term systemic effects: 260 mg/m³ Industry - Dermal; Long term systemic effects: 40 mg/kg/day

PNEC - Soil; 23.5 mg/kg - Marine water; 15.4 mg/l - Intermittent release; 1540 mg/l - Sediment; 570.4 mg/kg - Fresh water; 154 mg/l - STP; 100 mg/l

Immediate danger to life and health 6000 ppm

ETHYLBENZENE (CAS: 100-41-4)

Immediate danger to life and health 800 ppm

HEPTANE (CAS: 142-82-5)

Immediate danger to life and health 750 ppm

TOLUENE (CAS: 108-88-3)

Immediate danger to life and health 500 ppm

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Wear protective gloves made of the following material: Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber).

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Do not smoke in work area.

Pressline Blanket Fix (USA)

Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. If ventilation is inadequate, suitable respiratory protection must be worn. Wear a supplied-air respirator. Wear self-contained breathing apparatus.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Viscous liquid. Liquid.
Color	Water-white.
Odor	Chlorinated hydrocarbons.
Odor threshold	No information available.
pH	Not applicable.
Melting point	Not applicable.
Initial boiling point and range	104°F @ 760 mm Hg
Flash point	None°C TCC (Tag closed cup).
Evaporation rate	<1 (butyl acetate = 1)
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 14 % Upper flammable/explosive limit: 22 % Dichloromethane
Vapour pressure	340 mm Hg @ 20°C
Vapour density	>1
Relative density	1.32 @ 20°C
Bulk density	Not applicable.
Solubility(ies)	Immiscible with water.
Partition coefficient	: 1.25 Dichloromethane
Auto-ignition temperature	556°C Dichloromethane
Decomposition Temperature	No information available.
Viscosity	No information available.
Oxidising properties	Not applicable.
Comments	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.
Volatile organic compound	This product contains a maximum VOC content of 654 g/litre. This product contains a maximum VOC content of 5.5 lb per Gallon.

10. Stability and reactivity

Reactivity	The following materials may react strongly with the product: Alkaline earth metals. Powdered metal.
Stability	Stable at normal ambient temperatures.
Possibility of hazardous reactions	Will not polymerize.

Pressline Blanket Fix (USA)

Conditions to avoid	Avoid heat.
Materials to avoid	Strong oxidizing agents. Strong reducing agents. Strong acids. Strong alkalis. Alkali metals. Powdered metal.
Hazardous decomposition products	Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂). Hydrogen chloride (HCl). Phosgene (COCl ₂).

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Harmful if swallowed.

ATE oral (mg/kg) 389.86354776

Acute toxicity - dermal

Notes (dermal LD₅₀) Harmful in contact with skin.

ATE dermal (mg/kg) 1,113.02236163

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Harmful by inhalation.

ATE inhalation (gases ppm) 2,633.61411283

ATE inhalation (vapours mg/l) 10.99725069

ATE inhalation (dusts/mists mg/l) 1.80886343

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro No specific test data are available. May cause genetic defects.

Carcinogenicity

Carcinogenicity No specific test data are available. Contains a substance/a group of substances which may cause cancer.

Reproductive toxicity

Reproductive toxicity - fertility No specific test data are available. Suspected of damaging fertility or the unborn child.

Specific target organ toxicity - single exposure

STOT - single exposure Drowsiness, dizziness, disorientation, vertigo. Gas or vapor in high concentrations may irritate the respiratory system. Causes damage to organs (Central nervous system , optic nerve).

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Contains toluene xylene ethylbenzene May cause damage to organs (Central nervous system , Liver , Kidneys , Hearing organs) through prolonged or repeated exposure.

Pressline Blanket Fix (USA)

Target organs	Central nervous system Liver Kidneys Hearing organs
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.
<u>General information</u>	
General information	May cause damage to organs (Central nervous system , Liver , Kidneys , Hearing organs) through prolonged or repeated exposure. Causes damage to organs (Central nervous system , optic nerve).
Inhalation	Harmful by inhalation. Vapors in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. May cause respiratory system irritation.
Ingestion	Harmful if swallowed. Ingestion of large amounts may cause unconsciousness. May cause nausea, headache, dizziness and intoxication. May cause stomach pain or vomiting.
Skin Contact	Harmful in contact with skin. This product is strongly irritating. Prolonged contact may cause burns. Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. Contains components which may penetrate the skin. Irritating.
Eye contact	May cause severe eye irritation. May cause chemical eye burns.
Acute and chronic health hazards	Contains a substance/a group of substances which may cause cancer. Suspected of damaging fertility or the unborn child. May cause genetic defects.
Route of entry	Inhalation Skin absorption Ingestion. Skin and/or eye contact
Target Organs	Skin Eyes Respiratory system, lungs Central nervous system Kidneys Liver Heart & cardiovascular system optic nerve Hearing organs
Medical Symptoms	Skin irritation. Dry skin. Irritation of eyes and mucous membranes. Drowsiness, dizziness, disorientation, vertigo. Central nervous system depression. May cause cancer after repeated exposure. Causes serious eye damage. Kidney damage. Liver damage. Chemical burns.

12. Ecological Information

Ecotoxicity Not known. The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. However, this preparation has not been classified as hazardous to the environment using the conventional method calculation.

Toxicity

Acute toxicity - fish Not known.

Acute toxicity - aquatic invertebrates Not known.

Acute toxicity - aquatic plants Not known.

Ecological information on ingredients.

Solvent naphtha (petroleum), light aliph.

Acute toxicity - fish	LC ₅₀ , 96 hours: 8.2 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 4.5 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: 3.7 mg/l, Pseudokirchneriella subcapitata

Pressline Blanket Fix (USA)

Persistence and degradability

Persistence and degradability The product is not expected to be biodegradable.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient : 1.25 Dichloromethane

Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product has poor water-solubility.

Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations

Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

UN Number

UN No. (DOT) 2810

UN No. (IMDG) 2810

UN No. (ICAO) 2810

UN proper shipping name

Proper shipping name (DOT) TOXIC LIQUID, ORGANIC, N.O.S. (PETROLEUM DISTILLATES N.O.S., TETRACHLOROETHYLENE)

Proper shipping name (IMDG) TOXIC LIQUID, ORGANIC, N.O.S. (PETROLEUM DISTILLATES N.O.S., TETRACHLOROETHYLENE)

Proper shipping name (ICAO) TOXIC LIQUID, ORGANIC, N.O.S. (PETROLEUM DISTILLATES N.O.S., TETRACHLOROETHYLENE)

Transport hazard class(es)

IMDG Class 6.1

ICAO class/division 6.1

Transport labels



Packing group

Pressline Blanket Fix (USA)

DOT pack group III

IMDG packing group III

ICAO packing group III

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

EmS F-A, S-A

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

International Regulations

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

Not listed

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

DICHLOROMETHANE

30-60%

METHANOL

10-30%

NAPHTHALENE

<0.01%

BENZENE

<0.01%

TOLUENE

1-5%

ETHYLBENZENE

1-5%

XYLENE

1-5%

XYLENE-meta

<0.1%

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

Not listed

SARA 313 Emission Reporting

DICHLOROMETHANE

30-60%

Pressline Blanket Fix (USA)

METHANOL

10-30%

TOLUENE

1-5%

ETHYLBENZENE

1-5%

XYLENE

1-5%

CAA Accidental Release Prevention

Not listed

FDA - Essential Chemical

Not listed

FDA - Precursor Chemical

Not listed

OSHA Highly Hazardous Chemicals

Not listed

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

DICHLOROMETHANE

30-60%

METHANOL

10-30%

NAPHTHALENE

<0.01%

BENZENE

<0.01%

TOLUENE

1-5%

ETHYLBENZENE

1-5%

California Air Toxics "Hot Spots" (A-I)

DICHLOROMETHANE

30-60%

METHANOL

10-30%

NAPHTHALENE

<0.01%

BENZENE

<0.01%

TOLUENE

1-5%

Pressline Blanket Fix (USA)

ETHYLBENZENE

1-5%

XYLENE

1-5%

XYLENE-meta

<0.1%

California Air Toxics "Hot Spots" (A-II)

Not listed

California Directors List of Hazardous Substances

DICHLOROMETHANE

30-60%

METHANOL

10-30%

NAPHTHALENE

<0.01%

BENZENE

<0.01%

OCTANE

<1%

TOLUENE

1-5%

ETHYLBENZENE

1-5%

HEPTANE

1-5%

XYLENE

1-5%

XYLENE-meta

<0.1%

Massachusetts "Right To Know" List

DICHLOROMETHANE

30-60%

METHANOL

10-30%

NAPHTHALENE

<0.01%

BENZENE

<0.01%

OCTANE

<1%

TOLUENE

1-5%

Pressline Blanket Fix (USA)

ETHYLBENZENE

1-5%

HEPTANE

1-5%

XYLENE

1-5%

XYLENE-meta

<0.1%

Rhode Island "Right To Know" List

DICHLOROMETHANE

30-60%

METHANOL

10-30%

NAPHTHALENE

<0.01%

BENZENE

<0.01%

OCTANE

<1%

TOLUENE

1-5%

ETHYLBENZENE

1-5%

HEPTANE

1-5%

XYLENE

1-5%

Minnesota "Right To Know" List

DICHLOROMETHANE

30-60%

METHANOL

10-30%

NAPHTHALENE

<0.01%

BENZENE

<0.01%

OCTANE

<1%

TOLUENE

1-5%

ETHYLBENZENE

1-5%

HEPTANE

1-5%

Pressline Blanket Fix (USA)

XYLENE

1-5%

New Jersey "Right To Know" List

DICHLOROMETHANE

30-60%

METHANOL

10-30%

NAPHTHALENE

<0.01%

BENZENE

<0.01%

OCTANE

<1%

TOLUENE

1-5%

ETHYLBENZENE

1-5%

HEPTANE

1-5%

XYLENE

1-5%

XYLENE-meta

<0.1%

Pennsylvania "Right To Know" List

DICHLOROMETHANE

30-60%

METHANOL

10-30%

NAPHTHALENE

<0.01%

BENZENE

<0.01%

OCTANE

<1%

TOLUENE

1-5%

ETHYLBENZENE

1-5%

HEPTANE

1-5%

XYLENE

1-5%

XYLENE-meta

<0.1%

Pressline Blanket Fix (USA)

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.
DSL

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

Not listed

16. Other information

Key literature references and sources for data Material Safety Data Sheet, Misc. manufacturers.

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by J Waterfield

Revision date 6/14/2015

Revision 2.0

Supersedes date 8/1/2014

SDS No. 21226

Hazard statements in full

H225 Highly flammable liquid and vapor.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H340 May cause genetic defects.
H350 May cause cancer.
H361d Suspected of damaging the unborn child.
H370 Causes damage to organs (Central nervous system , Eyes).
H370 Causes damage to organs .
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

ACA HMIS Health rating. Moderate hazard. (2)

ACA HMIS Physical hazard rating. Normally stable. (0)

ACA HMIS Personal protection rating. C

ACA HMIS Flammability rating. Burns only if pre-heated. (1)

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.