

# MATERIAL SAFETY DATA SHEET

SHEET FED OFFSET LIGHT FASTNESS INK

PAGE 1 OF 2

MANUFACTURER ; Tokyo Printing Ink Mfg. Co., Ltd.  
ADDRESS ; 2-7-15 Tabatashinmachi, Kita-ku, Tokyo, Japan  
TELEPHONE NO. ; TOKYO(03) 3893 5151  
DATE PREPARED ; May 24, 2004

## SECTION. 1 PRODUCT IDENTIFICATION

COMMON NAME ; Sheet-Fed Offset-Printing Light-Fastness Ink  
PRODUCT NAME ; Permanent – Reflex Blue, Violet, Purple, Rhodamine Red

## SECTION. 2 HAZARDOUS INGREDIENTS

COMPONENTS	CAS No.	WT. %	
Hydrotreated Petroleum Hydrocarbon	64742-46-7	34-38	
Rosin Modified Phenolic Resin	68082-96-2	30-34	
Linseed Oil Modified Alkyd Resin	67700-81-6	10-13	
Isoocta Decanol	27458-93-1	1	
Polyethylene Wax	9002-88-4	1	
<u>Organic Pigment</u>			
Reflex Blue	C.I. Pigment Blue 15	147-14-8	18
	C.I. Pigment Violet 23	6358-46-6	0.5
Violet	C.I. Pigment Violet 23	6358-46-6	13
	C.I. Pigment Blue 15	147-14-8	0.5
Purple	C.I. Pigment Red 122	16043-40-6	13.5
	C.I. Pigment Violet 23	6358-46-6	0.3
Rhodamine Red	C.I. Pigment Red 122	16043-40-6	21
	C.I. Pigment Red 188	31847-48-1	0.3

Generally Classified as Non Toxic

## SECTION. 3 PHYSICAL DATA

APPEARANCE ; Viscous Paste  
COLOR ; Various  
ODOR ; Oily Odor  
MOLECULAR WEIGHT ; NE  
PH ; NE  
SPECIFIC GRAVITY ; 0.95-1.03 (25°C)  
BOILING POINT ; NE  
VAPOR DENSITY ; NE  
VAPOR PRESSURE ; NE  
SOLUBILITY IN WATER ; Insoluble

## SECTION. 4 FIRE AND EXPROSION DATA

FLASH POINT ; 150-160°C (Open Air)  
FLAMMABLE LIMITS / UPPER ; NE LOWER ; NE  
EXTINGUISH MEDIA ; Water, Fog, Foam, Dry Chemical  
SPECIAL FIRE FIGHTING PROCEDURES ; Keep out of smoke. Self contained breathing apparatus is recommended.

UNUSUAL FIRE AND EXPROSION HAZARDS ; NE

---

SECTION. 5 HEALTH HAZARD DATA

---

EFFECTS OF OVEREXPOSURE

---

INHALATION ; May cause respiratory irritation and dizziness.  
SKIN ; May cause irritation, defatting, allergic contact dermatitis and sensitization.  
EYE ; Will cause severe irritation.  
INGESTION ; May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

---

EMERGENCY FIRST AID PROCEDURE

---

INHALATION ; Move to fresh air. Aid in breathing and get medical attention, if necessary.  
SKIN ; Remove contaminated clothing and wash well with soap and water.  
EYE ; Flush with plenty water immediately for at least 15 min. and get medical attention.  
INGESTION ; Drink a large quantity of water. If available, milk is better. Get medical attention.

---

SECTION. 6 REACTIVITY DATA

---

STABILITY ; Stable  
CONDITION TO AVOID ; Heat, Spark, Open flame  
INCOMPATIBILITY ; May react with strong oxidizing agents.  
HAZARDOUS DECOMPOSITION PRODUCTS ; may evolve noxious fumes such as carbon oxide, nitrous oxide when involved in a fire burning.  
HAZARDOUS POLYMERIZATION ; Not expected.

---

SECTION. 7 SPILL OR LEAK PROCEDURE

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED AND SPILLED ; Wipe out and placed in a suitable covered container for disposal.  
DISPOSAL METHOD ; Dispose in accordance with local, country, state and federal regulation.

---

SECTION. 8 PROTECTION MEASURES

---

RESPIRATION ; Use respirator, if necessary.  
VENTILATION ; Use general and local exhaust ventilation.  
SKIN ; Rubber gloves is recommended.  
EYE ; Safety glasses is recommended.  
OTHER ; Use apron, coverall and boots, if necessary.

---

SECTION. 9 SPECIAL PRECAUTIONS AND STORAGE DATA

---

PRECAUTION IN HANDLING AND STORING ; Store in sealed container and keep away from high temperature (40°C<), direct sunlight and excessive moisture.  
AVERAGE SHELF LIFE ; 6 months or more

---

NE ; Not Established.

---